TECHNICAL DATA SHEET

Iron Oxide Pigment



Iron Oxide Black 370

Edition of2016-12-16TypeBlack pigmentDelivery FormPowder

Chemical Class Synthetic iron oxide

Color Index Pigment Black 11(77499)

CAS No. 1317-61-9

Use RecommendationConstruction Industry

COLOR VALUES AND TINTING STRENGTH

Reference Standard: DIN 6174

| Min | Max | Test Method |
|------|----------------------|--|
| | R-706 | No.038.2009-08-01 |
| -0.7 | +0.7 | |
| -0.7 | +0.7 | |
| -0.7 | +0.7 | |
| | 1.0 | |
| | R-05 | |
| 95 | 105 | No.038.2009-08-01 |
| | -0.7 -0.7 -0.7 | R-706 -0.7 +0.7 -0.7 +0.7 -0.7 +0.7 1.0 R-05 |

TECHNICAL DATA

| | Min | | Max | Test Method |
|------------------------------------|------|-----------|-----|--------------------|
| Water-Soluble Content [%] | | | 1.0 | DIN ISO787 Part 3 |
| Sieve Residue (0.045mm) [%] | | | 0.5 | DIN 53195 |
| Fe ₂ O ₃ [%] | 95.0 | | | DIN 55913 Sheet 2 |
| Moisture (After Production) [%] | | | 1.0 | DIN ISO787 Part 2 |
| Particle Shape | | Spherical | | |

TECHNICAL DATA SHEET

Iron Oxide Pigment



Iron Oxide Black 370

| Approx. | |
|---------|---------------------|
| 0.2 | Electron Micrograph |

Density **[g/ml]** 4.5 DIN ISO787 Part 10(1995)

STANDARD PACKAGING 25kg/bag

TRANSPORT AND STORAGE

Predominant Particle size [µM]

Protect against weathering. Store in a dry place and avoid extreme fluctuations in temperature. Special conditions for opened packaging: Close bags after use to prevent the absorption of moisture and contamination.

SAFETY

The product is not classified as dangerous under the relevant EC directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to transport regulations. In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labeling and transport of dangerous substances must be ensured.

The information contained in the safety data sheet should be observed.

This contains information on handing, product safety and ecology.

This information is given in good faith, without warranty. It is also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General conditions of sale and delivery.

HANGZHOU XCOLOR

Tel:86-571-83885088 Fax:86-571-83885208

<u>www.xcolor.net</u> <u>Email: sales@xcolor.net</u> <u>info@xcolor.net</u>